



Investigation of Negative Ion Production in an Ar/CF₄ Matrix-ECR Plasma Source with Transversal Magnetic Filter

Baele, Pierre; Draghici, Mihai; Stamate, Eugen

Publication date:
2010

[Link back to DTU Orbit](#)

Citation (APA):

Baele, P., Draghici, M., & Stamate, E. (2010). *Investigation of Negative Ion Production in an Ar/CF₄ Matrix-ECR Plasma Source with Transversal Magnetic Filter*. Abstract from 63rd Annual Gaseous Electronics Conference and 7th International Conference on Reactive Plasmas, Paris, France.

General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

Abstract Submitted
for the GEC10 Meeting of
The American Physical Society

Sorting Category: 2.16 (E)

**Investigation of Negative Ion Production in an Ar/CF₄
Matrix-ECR Plasma Source with Transversal Magnetic Filter**

PIERRE BAELE, MIHAI DRAGHICI, EUGEN STAMATE, Risoe DTU, Technical University of Denmark, PLASMA PROCESSING COLLABORATION — Dry etching performed in plasma discharges is a key process in micro- and nanoelectronics industry. Recently, a considerable effort was dedicated to develop negative ion sources as an alternative solution for low-damage silicon etching using negative ions instead of positive ions. Despite of this interest, no plasma source using negative ions for etching at standards required in the processing industry has been developed so far. This work is reporting on negative ion production in Ar/CF₄ matrix-ECR plasma with a transversal magnetic filter. Mass spectrometry and probes are used for plasma diagnostics. A 4x3 matrix configuration of individual ECR plasma cells produced by Boreal Plasma is mounted at the top of a cubic chamber. Each cell includes a water cooled permanent magnet that provides a localized magnetic field necessary for electron cyclotron resonance. A water cooled magnetic filter is used to reduce the electron temperature. The negative ion spectrum is dominated by F⁻ and it depends on pressure, discharge power and Ar/CF₄ ratio. The density ratio of negative ion to electron was less than 3 for 3 mTorr in a power range up to 1800 W and reached 15 for 9 mTorr. Etching rates by positive ions and negative ions are reported for different discharge parameters.

☐ Prefer Oral Session
☒ Prefer Poster Session

Eugen Stamate
eust@risoe.dtu.dk
Technical University of Denmark

Date submitted: 12 Jun 2010

Electronic form version 1.4